

ENERGY AUTOMATION PRODUCTS




Motor protection Reyrolle 7SR57

[siemens.com/reyrolle](https://www.siemens.com/reyrolle)

The Reyrolle 7SR57 is a protective device engineered for comprehensive motor protection. It is utilized across various industrial settings and electrical systems to shield motors from potential damages caused by operational irregularities. The device boasts a broad spectrum of protection functions, flexible configurations for binary inputs/outputs, a wide-ranging power supply capability, and supports IEC 61850 Ethernet communications as a standard feature, enabling its easy integration into existing and automated energy systems.



Highlights

-  Compact design and low product life-cycle cost
-  Combined 1 A and 5 A current transformer inputs
-  28 programmable tri-color LEDs for clear indications

Benefits

- Reliable operation due to powerful, proven protection algorithms
- IEC 61850 Edition 1 & 2, DNP3 TCP, Modbus TCP with HSR, PRP and RSTP operation for increased availability
- Role Based Access Control (RBAC)
- Simple product ordering
- User selectable languages: English, French, German, Portuguese, Spanish, Turkish, Italian
- Conformal coating ordering option

Inputs and Outputs	<ul style="list-style-type: none"> • Current inputs – 4 or 8 • Voltage inputs – 0 or 4 • Binary inputs (max) – 29 • Binary outputs (max) incl. Device healthy contact – 16 • Arc flash detector inputs (AFD) – 0 or 3 • Heavy duty binary outputs (HDBO) – 0 or 4 • High speed binary outputs (HSBO) – 0 or 3 • Temperature sensor inputs (TSI) – 0, 8 or 16
Communication	Standard front USB port (for configuration using Reydisp Manager 2, a PC based software tool), rear RS485, 2 x RJ45 electrical ports or optional optical Ethernet connections
Housing	Size 6, 8 or 12 with withdrawable design
Display	Backlit 128 x 128 LCD with text and graphical display capabilities suitable for single line mimic diagrams

Applications

- Motor protection functions designed to protect during all motor starting and running sequences
- Thermal algorithm optimized to closely match the thermal characteristics of motors
- Thermal monitoring via plant temperature sensors supported
- Motor differential protection (87M) for large motors (7SR572 devices only)

Standard Functionality

- 14 Locked rotor protection
- 37/37G Undercurrent protection – phase/earth
- 46BC Broken conductor detection
- 46PR Phase-rotation reversal
- 46UB Phase unbalance
- 48 Starting-time supervision
- 49M Motor thermal overload protection
- 49TS Temperature sensor supervision
- 50/50G/50N Instantaneous overcurrent/earth fault
- 50AFD Arc flash detection
- 50BCL Break capacity limit
- 50BF Circuit-breaker failure protection – 3-pole
- 51/51G/51N Time delayed overcurrent/earth fault
- 52 Circuit-breaker control
- 60CTS CT supervision
- 66 Number of starts
- 74CC/74TC Close-circuit and trip-circuit supervision
- 81B Backspin monitor
- 81HB2 Inrush current detection
- 86 Lockout
- 87GH Restricted earth fault protection – high-impedance
- 87M Motor differential protection (7SR572)

Additional Functionality – Devices with VT Inputs

- 27/27Vx Undervoltage protection
- 32 Power protection
- 47 Sequence overvoltage protection
- 55 Power factor
- 59/59Vx Overvoltage protection
- 59N Neutral voltage displacement
- 60VTS VT supervision
- 67/67G/67N Directional – phase/earth fault
- 81 Frequency protection – „f>“ or „f<“
- 81B-V Backspin monitor – voltage reference

Monitoring Functions


- Primary, secondary, phase sequence, current & voltage
- Frequency, power, and energy
- Fault data, event and waveform records
- Motor start data log


Security Features


- Signed firmware
- Encrypted connection between the device and PC tool
- Security logging
- Separate firmwares for protection and communication
- Secure access with password control
- Role based access control
- Encrypted WebUI access


Communication


- IEC 60870-5-103, DNP3, Modbus RTU, Modbus Client (for use with external TSI interface), IEC 61850, DNP3 TCP, Modbus TCP

 [Virtual Relay Tool](#)

 [Configuration software - Reydisp Manager](#)

 [Webinar series - Reyrolle essentials](#)

 [Catalog Reyrolle 7SR5 Platform](#)

 [Online shop - Industry Mall](#)

Siemens AG

Smart Infrastructure
Electrification & Automation
Mozartstrasse 31c,
91052 Erlangen, Germany

Siemens Industry Inc.
3617 Parkway Lane
Peachtree Corners, GA 30092
United States

© Siemens 2024

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.